LED EXIT & EMERGENCY



LED EXIT & EMERGENCY EXIT & COMBO SIGNS





- Maintenance-free nickel-cadmium battery (RC version nickel-metal hydride)
- Energy-saving LED
- Injection-molded, high-impact, UV-stabilized, UL94 V-0 thermoplastic construction
- Top, back, J-box or end mounting through universal mounting plate and canopy
- RC version provides 3.44 watts for 90 minutes

CATALOG #	DESCRIPTION	FINISH	LETTER COLOR	VOLTS
EXPRWR	Thermoplastic Exit Sign	White	Red	120/277
EXPRWG	Thermoplastic Exit Sign	White	Green	120/277
EXPRWRRC	Thermoplastic Exit Sign - Remote Capable	White	Red	120/277
EXPRWGRC	Thermoplastic Exit Sign - Remote Capable	White	Green	120/277





Scan **QR CODE** for more information

quick SHIP

Scan QR CODE

for more information



EXIT

- Maintenance-free nickel-cadmium battery (RC version nickel-metal hydride)
- Energy-saving LED
- Injection-molded, high-impact, UV-stabilized, UL94 V-0 thermoplastic construction
- Top, back, J-box or end mounting through universal mounting plate and canopy
- RC version provides 3.44 watts for 90 minutes

CATALOG #	DESCRIPTION	FINISH	LETTER COLOR	VOLTS
EECPRWR	Thermoplastic LED Exit/Emergency Combo	White	Red	120/277
EECPRWG	Thermoplastic LED Exit/Emergency Combo	White	Green	120/277
EECPRWRRC	Thermoplastic LED Exit/Emergency Combo - Remote Capable	White	Red	120/277
EECPRWGRC	Thermoplastic LED Exit/Emergency Combo - Remote Capable	White	Green	120/277

LED EXIT & EMERGENCY EMERGENCY LIGHTING



Scan **QR CODE** for more information

OVAL 2 HEADED EMERGENCY LIGHT



- Maintenance-free nickel-cadmium battery (RC version nickel-metal hydride)
- Injection-molded, high-impact, UV-stabilized, UL94 V-0 thermoplastic construction
- Universal J-box pattern knock-out & mounting plate w/ quick connect features
- Fully adjustable glare free LED heads
- RC version provides 3.44 watts for 90 minutes

CATALOG #	DESCRIPTION	FINISH	VOLTS
EMO2A	Oval 2 headed emergency light	White	120/277
EMO2ARC	Oval 2 headed emergency light - Remote Capable	White	120/277



Scan **QR CODE** for more information

ARCHITECTURAL EMERGENCY LIGHT

- Long-life, efficient ultra-bright white LED
- Mirror-bright reflector and prismatic polycarbonate refractor
- Die-cast aluminum housing
- Durable powder-coated finish
- Sealed and gasketed
- Cold-weather unit for use in temperatures as low as -20°C 40°C

CATALOG #	DESCRIPTION	FINISH	VOLTS
ERD12BZ	Architectural LED Emergency Light	Bronze	120/277



Scan **QR CODE** for more information





- Weatherproof plastic housing with LED assembly
- Rated for indoor/outdoor use

CATALOG #	DESCRIPTION	VOLTAGE	TOTAL WATTAGE
ERHR12	Single Remote Head - Indoor/Outdoor	3.6 Volts	1.17 Watts
ERHR22	Double Remote Head - Indoor/Outdoor	3.6 Volts	2.34 Watts

LED EXIT & EMERGENCY

LIGHTING



PO BOX 2348 BURLINGTON, NC 27216 1406 S. MEBANE STREET BURLINGTON, NC 27215 800-849-8485 | FAX 1-855-847-2794 WWW.ATLASLED.COM

452-246 092518



to visit our website

