



Classic Series
Full Cut Off Wall Light

PROJECT INFORMATION

JOB NAME	
FIXTURE TYPE	Full Cut Off Wall Light
CATALOG NUMBER	
APPROVED BY	

SPECIFICATIONS

Construction:

Rugged Traditional aluminum die cast housing provides proven environmental protection for LED modules. Traditional fixture design provides a familiar look and standard installation requirements. Retaining this look allows the ability to upgrade fixtures gradually, while retaining the same overall fixture appearance throughout a facility.

Glare Free:

Positioning of the LED modules within the housing result in light directed to desired locations and eliminates offensive light.

Thermal Management:

Atlas' Patent Pending exclusive Thermal Management System™ features a unique internal design that allows for lower operating temperatures which results in a brighter, whiter light, more stable color and longer LED and driver life.

Listings:

Luminaire is certified to UL/cUL Standards for Wet Locations

AC Input: 120/208/240/277V

Driver:

Constant current, Class 2, 120-277 VAC, 50-60 Hz

High Efficiency – min. 84%

Off-State Power: 0 Watts

0-10 V Dimming

LEDs:

3000K | 4000K | 4500K | 5000K CCT

Epoxy Guard™ protective conformal coated boards

Atlas LEDs provide higher lumen output, greater energy efficiency and more reliable fixture performance.

L80 Calculated Life: >200,000 Hours¹

Testing:

Atlas LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 & LM-80.

Warranty: Five-year limited warranty

Installation:

Fixture retains the same knock-out sizes and positions as previous models, reducing wiring costs.

Photo Control: For factory installed 120V button photo control add suffix PC to part number.



Emergency Back-up: Factory-installed emergency backup available for WLMFC by adding EB suffix to part number.



DIMENSIONS



WLCFC

Weight: 8 lbs.




WLMFC

Weight: 14 lbs.



MOUNTING DETAIL



¹LED Life Span Based Upon LM-70 Test Results

Rebates and Incentives are available in many areas.
Contact an Atlas Representative for more information.

*The majority of Atlas Lighting Products are assembled in USA facilities by an American Workforce utilizing both Domestic and Foreign components. Meets Buy American requirements within the ARRA.



Classic Series
Full Cut Off Wall Light

ORDERING INFORMATION

WLMFC	43LED					
PRODUCT SERIES	WATTAGE	COLOR TEMP.	CONTROLS	VOLTAGE	FIXTURE COLOR	OPTIONS
WLCFC = Small Full Cut Off Wall Light WLMFC = Medium Full Cut Off Wall Light	27LED = 27 Watts ¹ 43LED = 43 Watts ² 64LED = 64 Watts ² ¹ WLCFC only ² WLMFC only	Blank = 4500K 3K = 3000K 4K = 4000K 5K = 5000K	Blank = Dimming (0-10V) PC = 120V Photocontrol PM = 120-277V Photocontrol	Blank = 120-277	Blank = Bronze WT = White* BK = Black* <i>*optional with adder</i>	EB = Emergency Back-up* <i>*WLMFC only</i>

PERFORMANCE DATA

UNIT	CRI	3000K CCT		4000K CCT		4500K CCT		5000K CCT		WATTAGE	REPLACES UP TO
		DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)		
27LED	81	3,140	121	3,140	121	3,411	129	3,411	129	26	100W MH
43LED	81	5,151	125	5,151	125	5,366	130	5,366	130	41	175W MH
64LED	81	7,746	124	7,746	124	8,131	132	8,131	132	63	400W MH